

Industrial Mill

HGM-SERIES



Liming Heavy Industry

www.break-day.com



Industrial Mill

HGM-SERIES

Features

Three-Ring & Medium-Speed MicroPowder Mill has high efficiency and low cost. Its capacity is raised by 40% compared with airflow mill and mix mill on the condition that the materials, the drive and the fineness of the final powder are the same. The life span of tear & wear parts is more than that of straight impact crusher and turbine mill under the circumstance of same materials and fineness of the final powder. Usually, its life span is more than one year. There is no rolling bearing and screw in the grinding cavity, so as to avoid the damage to the machine caused by tear & wear of bearing and seals and the looseness of screws. The fineness of powder can reach $\leq 5\mu\text{m}$ with d97 once.



Industrial Mill

HGM-SERIES

Working Principle

The motor drives the main shaft and every turnplate through the reducer. The reducer drives dozens of rollers to rotate against race way of ring through pin. Small material crushed by hammer crusher is transported into hopper by elevator, and then vibrating feeder shall feed material to the central part of upper turnplate evenly. The material falls to circle under the centrifugal force and comes down to raceway of ring to be crushed into powder. After grinded in the first race way, the material goes to the second and third turnplate. The blower inhales the external air into the mill and carries the powder after third turnplate into powder-separator. Turbine in the separator makes the coarse powder drop down and regrinded and the fine powder shall go into cyclone powder collector together with air current and go down through discharge valve as final product; at the same time, air current with a little dust goes out through blower and muffler after purified by filter.



Specifications

Model	HGM60	HGM80	HGM100
Roller number	15	21	27
Diameter (mm)	Φ600	Φ800	Φ1000
Ring number	2	2	2
Main unit speed(mm)	235	235	235
Max. feeding size(mm)	10	10	10
Final size (mesh)	325-2500	325-2500	325-2500
Capacity (kg/h)	350-2500	600-4000	900-6000
Overall dimension (m)	10×2×5.5	12.4×2.5×5.8	14.5×3.8×6.3

Notice: Any change of Ball Mill technical data shall not be advised additionally.

Contact us

Tel: 0086-371-67992899
0086-371-67371699
Fax: 0086-371-67992699
E-mail: info@limingco.com
MSN:
SalesCrusher@hotmail.com
www.break-day.com



Production Line Configuration

The whole set HGM Micro Powder Grinding Mill consists of(see sketch 1)hammer crusher,bucket elevator,storage hopper,vibrating feeder,main unit,inverter classifier,cyclone,pulse bag filter system,high pressure positive blower, air compressors and electrical control systems.

